

E43 P series

108mm~370mm

General Specifications

- Motor : Shaded pole AC motor
- Frame & Impeller : Metal
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +65°



Major Characteristic Parameters

Model	Size(mm)			Rated Voltage	Rated Frequency	Rated Current	Input Power	Rated Speed	Maximum Air Flow		Maximum Static Pressure		Sound Level	Weight
	Part NO.	A	B						C	V	Hz	A		
CE43090A11	98	108	160	110	60	0.12	9	3000	1.1	38.86	1.2	0.047	38	520
CE43090A22	98	108	160	220	50	0.08	10	2600	0.9	31.80	0.9	0.035	36	520
CE43150A11	160	170	222	110	60	0.13	10	2500	1.5	53.00	1.5	0.059	39	550
CE43150A22	160	170	222	220	50	0.07	11	2500	1.4	49.46	1.2	0.047	38	550
CE43190A11	198	208	264	110	60	0.19	14	2500	2.2	77.7	1.8	0.070	39	650
CE43190A22	198	208	264	220	50	0.08	13	2400	2.1	74.20	1.4	0.055	39	650
CE43240A11	250	260	315	110	60	0.20	15	2300	2.3	81.27	1.8	0.070	41	680
CE43240A22	250	260	315	220	50	0.09	14	2300	2.3	81.27	1.5	0.059	40	680
CE43290A11	300	310	375	110	60	0.26	21	2800	2.7	95.40	1.4	0.055	44	890
CE43290A22	300	310	375	220	50	0.14	19	2550	2.5	88.33	1.5	0.059	41	890
CE43350A11	360	370	435	110	60	0.32	23	2500	3.3	116.60	1.3	0.051	46	920
CE43350A22	360	370	435	220	50	0.15	20	2450	3.2	113.07	1.6	0.062	46	920

