

# E60 F series

138mm~444mm

## General Specifications

- Motor : Shaded pole AC motor
- Frame & Impeller : Metal
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +65°



## Major Characteristic Parameters

Model	Size(mm)			Rated Voltage	Rated Frequency	Rated Current	Input Power	Rated Speed	Maximum Air Flow		Maximum Static Pressure		Sound Level	Weight
	Part NO.	A	B						C	V	Hz	A		
CE60120A11	123	138	191	110	60	0.23	18	2350	1.7	60.07	2.7	0.106	43	1200
CE60120A22	123	138	191	220	50	0.12	18	2350	1.7	60.07	2.5	0.098	43	1200
CE60180A11	184	199	162	110	60	0.58	41	2500	2.9	102.47	4.8	0.188	47	1350
CE60180A22	184	199	162	220	50	0.26	32	2500	2.9	102.47	4.0	0.157	47	1350
CE60240A11	306	321	384	110	60	0.59	40	2100	2.9	102.47	3.7	0.145	44	1400
CE60240A22	306	321	384	220	50	0.27	35	2200	3.5	123.67	4.0	0.157	46	1400
CE60300A11	306	321	384	110	60	0.60	41	2000	3.7	130.742	3.4	0.133	44	1500
CE60300A22	306	321	384	220	50	0.30	41	2100	4.0	141.34	3.6	0.141	46	1500
CE60360A11	368	383	446	110	60	0.61	42	1700	3.9	137.80	2.8	0.110	40	1600
CE60360A22	368	383	446	220	50	0.31	42	2000	4.7	166.07	3.5	0.137	46	1600
CE60420A11	429	444	507	110	60	0.62	42	1600	4.8	169.61	2.5	0.098	40	1650
CE60420A22	429	444	507	220	50	0.31	42	1800	5.3	187.27	2.9	0.114	45	1650

