

# 70 AG series

x70x15mm



## General Specifications

- Motor : 4 Poles brushless DC motor
- Frame & Impeller : Plastic(UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

## Major Characteristic Parameters

Model	*Bearing System	Rated Voltage	Operating Voltage Range	Rated Current	Rated Speed	Maximum Air Flow		Maximum Static Pressure		Sound Level	Weight
Part NO.	B / S / F	V	V	A	RPM	m <sup>3</sup> /min	CFM	mm-H <sub>2</sub> O	In-H <sub>2</sub> O	dBA	g
AGE07015_12J	B / S	12	7.0~13.2	0.10	2800	0.60	21.1	2.3	0.09	27.0	50
AGE07015_12L	B / S	12	7.0~13.2	0.12	3300	0.73	25.7	3.3	0.13	31.0	50
AGE07015_12M	B / S	12	7.0~13.2	0.17	3800	0.84	29.6	4.3	0.17	35.0	50
AGE07015_12H	B / S	12	7.0~13.2	0.25	4300	0.95	33.5	5.5	0.22	39.0	50

\*Bearing system B: Two Ball Bearing F: Fluid Bearing S: Sleeve Bearing

